

Mirathane™ M95

Thermoplastic Polyurethane Elastomer (Polyether)

Miracll Chemicals Co., Ltd.

Message:

Mirathane™ M95 is a Thermoplastic Polyurethane Elastomer (Polyether) (TPU-Polyether) product. It is available in Asia Pacific. Applications of Mirathane™ M95 include hose/tubing, additive/masterbatch, agricultural, coating applications and film.

General Information			
Uses	Compounding		
	Fabric Coatings		
	Film		
	Hose		
	Molded Ear Tags		
	Sheet		
	Tubing		
	Wire & Cable Applications		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.14	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shore A	95		
Shore D	53		
Mechanical	Nominal Value	Unit	Test Method
Taber Abrasion Resistance	35.0	mg	ASTM D1044
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress			ASTM D412
100% Strain	8.00	MPa	
300% Strain	14.0	MPa	
Tensile Strength (Yield)	32.0	MPa	ASTM D412
Tensile Elongation (Break)	450	%	ASTM D412
Tear Strength	110	kN/m	ASTM D624
Compression Set			ASTM D395
23°C, 72 hr	30	%	
70°C, 22 hr	70	%	
Thermal	Nominal Value	Unit	Test Method
Glass Transition Temperature ¹	-35.0	°C	ASTM D3417
NOTE			

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

