

POLYFLON™ D-3A

Polytetrafluoroethylene

DAIKIN AMERICA, INC.

Message:

Daikin-Polyflon PTFE D-3A is a modified polytetrafluoroethylene aqueous dispersion. D-3A has been specifically designed for use in release coating and glass cloth impregnation applications where improved gloss, adhesion, surface smoothness and wear properties are desired. D-3A contains a more environmentally friendly surfactant that leaves fewer residues in the substrate than traditional surfactants.

General Information			
Features	Highlight		
	Good adhesion		
	Good wear resistance		
	Excellent appearance		
Uses	Coating application		
Appearance	White		
Forms	Particle		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.50	g/cm ³	ASTM D792

Additional Information			
Specific Gravity, hydrometer, 25°C: 1.50-1.53Viscosity, Daikin test method, 25°C: 15-25pH @ 25°C, ASTM D4441: 8.5-10Solids Content, ASTM D4441: 59-61%Surfactant Content, ASTM D4441: 6.2-7.8%			

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

