

APEX® 85-J501P-NT

Flexible Polyvinyl Chloride

Teknor Apex Company

Message:

APEX®85-J501P-NT is a flexible polyvinyl chloride material. This product is available in North America, Africa and the Middle East, Latin America, Europe or Asia Pacific. APEX®The main characteristics of 85-J501P-NT are: plasticization.
Typical application areas include:
Hose
medical/health care

General Information			
Features	Non-phthalate plasticizer		
Uses	Pipe fittings		
	Medical/nursing supplies		
Appearance	Clear/transparent		
Forms	Particle		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.27	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 15 sec)	85		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	21.9	MPa	ASTM D638
Tensile Elongation (Break)	350	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Continuous Use Temperature	105	°C	ASTM D794
Additional Information			

Apex 85-J501P-NT is a non-phthalate, polymeric plasticized, medical compound for extrusion with a durometer of 85 Shore A. All of the ingredients in this formulation can be found in 21CFR (Code of Federal Regulation) listed for use by the FDA for food contact applications.Additional Uses:
Surgical Wire Coating
Oxygen Delivery Systems
Wound Drainage Systems

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT