Electroblend® PP-1900

Polypropylene Homopolymer

Colour Image Plastic Compound Sdn. Bhd. (CIPC)

Message:

Electroblend® PP-1900 is a low flow antistatic polypropylene compound characterized by superb impact strength properties.

General Information				
Additive	Antistatic			
Features	Antistatic			
	High Impact Resistance			
	Low Flow			
Uses	Automotive Applications			
	Electrical/Electronic Applications			
	Industrial Parts			
Forms	Pellets			
Processing Method	Injection Molding			
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.00	g/cm³	ASTM D792	
Molding Shrinkage - Flow (3.20 mm)	1.2 to 1.4	%	ASTM D955	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength	28.0	МРа	ASTM D638	
Tensile Elongation (Break)	55	%	ASTM D638	
Flexural Modulus	1150	МРа	ASTM D790	
Flexural Strength	40.0	МРа	ASTM D790	
Impact	Nominal Value	Unit	Test Method	
Notched Izod Impact (23°C)	500	J/m	ASTM D256	
Thermal	Nominal Value	Unit	Test Method	
Deflection Temperature Under Load (0.45 MPa, Unannealed, 4.00 mm)	98.0	°C	ASTM D648	
Electrical	Nominal Value	Unit	Test Method	
Surface Resistivity	1.0E+3 to 1.0E+5	ohms	ASTM D257	
Flammability	Nominal Value	Unit	Test Method	
Flame Rating (1.60 mm)	НВ		UL 94	
Injection	Nominal Value	Unit		
Drying Temperature	80.0	°C		
Drying Time	2.0 to 4.0	hr		
Rear Temperature	185 to 190	°C		
Middle Temperature	190 to 195	°C		

Front Temperature	195 to 210	°C	
Nozzle Temperature	210 to 220	°C	
Processing (Melt) Temp	190 to 220	°C	
Mold Temperature	60.0 to 90.0	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

