

NEXUS PE HDPE-1252

High Density Polyethylene

Nexus Resin Group, LLC.

Message:

High Density Polyethylene for injection molding applications
Nexus HDPE-1252 is designed for injection molding applicationsrequiring good impact strength and stiffness.

General Information			
Features	Good Impact Resistance		
	Good Stiffness		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.952	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	12	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	26.9	MPa	ASTM D638
Tensile Elongation (Break)	900	%	ASTM D638
Flexural Modulus	1280	MPa	ASTM D790

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT