

Hax™ HF 28

Polyolefin
Fainplast Compounds S.r.l

Message:

Hax™ HF 28 is a Polyolefin product. It is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Typical application: Wire & Cable.
Characteristics include:
Flame Retardant
Halogen Free

General Information			
Additive	Flame Retardant		
Features	Flame Retardant		
	Halogen Free		
	Low Smoke Emission		
Uses	Cable Jacketing		
	Wire & Cable Applications		
Wire Types	HM2		
	HM5		
	M1		
	TI6		
Agency Ratings	EN 50363-0		
	EN 50363-7		
	EN 50363-8		
	VDE 0207/23		
	VDE 0250/215		
Physical	Nominal Value	Unit	Test Method
Density	1.48	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (280°C/0.325 kg)	4.0	g/10 min	ISO 1133
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore D, 15 sec)	50		ISO 868
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Break)	13.0	MPa	ISO 527-2
Tensile Strain (Break)	190	%	ISO 527-2
Electrical	Nominal Value	Unit	Test Method
Volume Resistivity (20°C)	3.0E+14	ohms · cm	IEC 60093
Flammability	Nominal Value	Unit	Test Method

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

