

# SolVin 260RF

Polyvinyl Chloride  
INOVYN

Message:

Polyvinyl chloride made by suspension polymerisation.  
APPLICATIONS:  
Fittings, electrical housings, bottles, rigid film, rigid foam.

| General Information             |                    |                   |             |
|---------------------------------|--------------------|-------------------|-------------|
| Features                        | High Rigidity      |                   |             |
| Uses                            | Bottles            |                   |             |
|                                 | Electrical Housing |                   |             |
|                                 | Film               |                   |             |
|                                 | Fittings           |                   |             |
|                                 | Foam               |                   |             |
|                                 | Sheet              |                   |             |
| Processing Method               | Calendering        |                   |             |
|                                 | Extrusion          |                   |             |
|                                 | Film Extrusion     |                   |             |
|                                 | Injection Molding  |                   |             |
| Physical                        | Nominal Value      | Unit              | Test Method |
| Apparent Density                | 0.56               | g/cm <sup>3</sup> | ISO 60      |
| K-Value                         | 60.0               |                   | ISO 1628-2  |
| Sieve Analysis                  |                    |                   | ISO 1624    |
| Retained on 0.063 mm sieve      | > 90               | %                 |             |
| Retained on 0.250 mm sieve      | < 2.0              | %                 |             |
| Volatile Matter                 | < 0.30             | %                 | ISO 1269    |
| Residual Vinyl Chloride Monomer | < 1.00             |                   | ISO 24538   |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT