Hostacom ERS 227N D61395

Polypropylene Copolymer

LyondellBasell Industries

Message:

Hostacom ERS 227N D61395 is an unfilled PP copolymer, with high flowability and high scratch resistance. Product is available as a customized color matched, pellet form. This grade is delivered in D61395 color version.

This grade is not intended for medical, pharmaceutical, food, drinking water and all applications not listed in the supported list. For more information please contact our sales representatives.

General Information			
Features	Copolymer		
	High liquidity		
	Scratch resistance		
Uses	Application in Automobile Field		
	Car exterior decoration		
Appearance	Available colors		
Forms	Particle		
Processing Method	Foam treatment		
	Injection molding		
Physical	Nominal Value	Unit	Test Method
Density (23°C)	0.920	g/cm³	ISO 1183/A
Melt Mass-Flow Rate (MFR) (230°C/2.16			
kg)	22	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Flexural Modulus ¹ (23°C)	1200	MPa	ISO 178/A
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact			ISO 180/1A
-30°C	3.0	kJ/m²	ISO 180/1A
23°C	15	kJ/m²	ISO 180/1A
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature (0.45 MPa			
Unannealed)	90.0	°C	ISO 75-2/B
NOTE			
1.	1.0 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

