

NITRIFLEX L-550

Acrylonitrile Butadiene Rubber

NITRIFLEX

Message:

NITRIFLEX L-550 is an Acrylonitrile Butadiene Rubber (NBR) product. It is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America.

General Information			
Forms	Latex		
Physical	Nominal Value	Unit	Test Method
Mooney Viscosity (100°C)	60 to 75	MU	ASTM D1646
Bound Acrylonitrile	27 to 31	%	ASTM D3533
pH (25°C)	8.0 to 9.0		ASTM D1417
Surface Tension	30 to 45	mN/m	ASTM D1417
Total Solids	38 to 42	%	ASTM D1417
Brookfield Viscosity - rotor n°1, spindle=1, 20 rpm	10 to 25	mPa·s	ASTM D1417
Coagulant - Content	0.0 to 0.10	%	ASTM D1417

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT