

Nipol® Roadstar

Latex

Zeon Corporation

Message:

Latex for pavements (SBR latex)

Characteristics

1. More aggregate gripping strength and adhesive strength (less aggregate spreading)
2. More flow resistance(less waving and grooving)
3. Excellent impact resistance (clutch prevention)
4. Excellent friction resistance (less friction in vehicles and chains)
5. Excellent age resistance(longer operating life)
6. Excellent waterproofing properties(peeling prevention)
7. Less brittleness caused by low temperatures(crack prevention)
8. Greater elasticity(improves traveling stability)

General Information		
Features	High Impact Resistance	
Physical	Nominal Value	Unit
Specific Gravity	0.978	g/cm ³
Solution Viscosity	130	mPa·s
Average Particle Size	50	nm
pH	10.0	
Total Solids	50	%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT