

Guang Sung PVC GPMA70

Flexible Polyvinyl Chloride

Guang Sung Plastics (GSPL)

Message:

Guang Sung PVC GPMA70 is a Flexible Polyvinyl Chloride product. It can be processed by extrusion and is available in Asia Pacific. Applications of Guang Sung PVC GPMA70 include adhesives/tapes, engineering/industrial parts and handles. Primary characteristic: rohs compliant.

General Information			
Uses	Handles		
	Shock Absorbing Pads		
	Tape		
RoHS Compliance	RoHS Compliant		
Forms	Pellets		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.25	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 5 sec)	73		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (100% Strain)	5.40	MPa	ASTM D412
Tensile Strength (Yield)	10.8	MPa	ASTM D412
Tensile Elongation (Break)	400	%	ASTM D412

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

