

Hostacom X M2 U34 82V Titan Schwarz

Polypropylene Homopolymer

LyondellBasell Industries

Message:

Hostacom X M2 U34 82V Titan Schwarz medium melt flow, very high flexural modulus, mineral-filled PP homopolymer has high stiffness, low odor and high heat ageing stability. It is offered with an interior UV weathering stabilization package and in a specific OEM color match, for select interior trim applications.

General Information			
Filler / Reinforcement	Mineral		
Additive	UV Stabilizer		
Features	Good Heat Aging Resistance High Stiffness Homopolymer Low to No Odor Medium Flow		
Uses	Automotive Applications Automotive Interior Trim		
Appearance	Black		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	1.06	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	10	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	34.0	MPa	ISO 527-2/50
Tensile Strain (Yield)	3.0	%	ISO 527-2/50
Flexural Modulus - Chord (23°C)	3100	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength (23°C)	3.0	kJ/m ²	ISO 179/1eA

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

