

Nylene® NX1170 HS

Polyamide 6
Custom Resins Group

Message:

Nylene NX 1170 HS is a high viscosity, heat stabilized grade formulated to give low wear properties through use of molybdenum disulfide at the 5 percent level.

General Information			
Additive	Heat Stabilizer		
	Molybdenum Disulfide Lubricant (5%)		
Features	Good Wear Resistance		
	Heat Stabilized		
	High Viscosity		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.31	g/cm ³	ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	75.8	MPa	ASTM D638
Tensile Elongation (Yield)	20	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Peak Melting Temperature	216	°C	ASTM D3418

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT