SEMICOSIL® 970 TC A/B

Silicone

Wacker Chemie AG

Message:

Silicone Rubber, RTV-2 Bonding & Sealing, Household Appliances Bonding & Sealing, Lighting Bonding & Sealing, Adhesives and Sealants

General Information

Uses Adhesives

Bonding

Electrical/Electronic Applications

Sealants

Uncured Properties	Nominal Value	Unit	Test Method
Color	White		
Density	2.26	g/cm³	DIN 53479
Viscosity	94	Pa∙s	ISO 3219
Pot Life	800	min	
Cured Properties	Nominal Value	Unit	Test Method
Shore Hardness (Shore A)	65		DIN 53505
Tensile Strength	4.00	MPa	ISO 37
Tensile Elongation at Break	90	%	ISO 37
Tear Strength	7.00	kN/m	ASTM D624B

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

