

# Kuraray Poval® PVA 105K

Polyvinyl Alcohol

Kuraray Co., Ltd.

## Message:

Fully hydrolysed grade - anti-foaming/defoaming grade

Mowiol® and Kuraray Poval® are the trade name of the polyvinyl alcohols marketed by Kuraray. These are manufactured from polyvinyl acetate by alcoholysis using a continuous process. By varying the degree of polymerization of the polyvinyl acetate and its degree of hydrolysis (saponification), a number of different grades can be supplied. Our PVOH types are offered in a high standard purity showing especially "low ash and VOC contents". Modification of emulsion adhesives, production of paper adhesives and remoistenable adhesives. Protective colloid in emulsion polymerisation and raw material for the production of sizes and textile finishes. Binder in the surface finishing of paper. Also for regulating the processing characteristics of all types of coatings.

| General Information               |  |         |             |
|-----------------------------------|--|---------|-------------|
| Features                          | Barrier Resin  |         |             |
|                                   | Biodegradable  |         |             |
|                                   | Good Adhesion  |         |             |
|                                   | Good Colorability  |         |             |
|                                   | Water Soluble  |         |             |
| Uses                              | Adhesives  |         |             |
|                                   | Binder   |         |             |
|                                   | Building Materials   |         |             |
|                                   | Coating Applications   |         |             |
|                                   | Film   |         |             |
|                                   | Foil Coatings  |         |             |
|                                   | Paper Coatings   |         |             |
|                                   | Textile Applications   |         |             |
| Forms                             | Granules   |         |             |
| Physical                          | Nominal Value  | Unit    | Test Method |
| Solution Viscosity <sup>1</sup>   | 5 to 6   | mPa · s | JIS K6726   |
| Ash Content <sup>2</sup>          | < 0.70   | %       |             |
| pH <sup>3</sup>                   | 4.5 to 7.0   |         |             |
| Volatile Matter                   | < 5.0  | %       |             |
| Degree of Hydrolysis <sup>4</sup> | 98 to 99   | %       |             |
| Methanol Extractables             | < 3.0  | %       |             |
| NOTE                              |  |         |             |
| 1.                                | 4 % aqueous solution at 20 °C,<br>determined by Brookfield<br>synchronised-motor rotary-type<br>viscometer |         |             |
| 2.                                | Calculated as Na2O   |         |             |
| 3.                                | 4 % solution in distilled water  |         |             |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

