

# PETILEN F2-21T

Low Density Polyethylene

PETKIM Petrokimya Holding A.S.

## Message:

PETILEN F2-21T is a Low Density Polyethylene product. It can be processed by film extrusion or sheet extrusion and is available in Asia Pacific, Europe, or North America. Applications of PETILEN F2-21T include packaging, coating applications, film, industrial applications and sheet.

General Information			
Uses	Film		
	Food Packaging		
	Industrial Applications		
	Laminates		
	Packaging		
	Sheet		
Forms	Pellets		
Processing Method	Film Extrusion		
	Sheet Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	0.919 to 0.923	g/cm <sup>3</sup>	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	2.1 to 2.9	g/10 min	ASTM D1238
Ash Content <sup>1</sup>	0.1	wt%	
Film Quality <sup>2</sup>	A		
Optical	Nominal Value	Unit	Test Method
Gloss	66		ASTM D2457
Haze	7.0	%	ASTM D1003
NOTE			
1.	ALKT-509		
2.	ALKATHENE 36		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT