# Geon™ Vinyl Flexible HC17080

### Flexible Polyvinyl Chloride

### PolyOne Corporation

### Message:

Geon™Vinyl Flexible HC17080 is a flexible polyvinyl chloride product. It can be processed by extrusion or injection molding and is available in North America, Africa and the Middle East, Latin America, Europe or Asia Pacific. Geon™Vinyl Flexible HC17080 applications include food contact applications and medical/health care.

Features include:

BPA free

NOTE

accessible food

plasticization

General Information

Features	Plasticized		
	Compliance of Food Exposure		
	BPA-free		
Uses	Medical devices		
Agency Ratings	FDA Food Exposure, Not Rated		
	FDA not rated		
	USP Class VI		
Appearance	Clear/transparent		
Forms	Particle		
Processing Method	Extrusion		
	Injection molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.22	g/cm³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 10 sec)	70		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus <sup>1</sup>	5.52	MPa	ASTM D412
Elastomers	Nominal Value	Unit	Test Method
Tensile Strength <sup>2</sup> (Break)	12.4	MPa	ASTM D412A
Tensile Elongation <sup>3</sup> (Break)	380	%	ASTM D412A
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-40.0	°C	ASTM D746
Additional Information			

仅为食品及药物管理局清单关于该产品内容的概述.由用户负责确保此化合物适用于其预期应用.

1.	Method A,20 inches/min
2.	510 mm/min
3.	510 mm/min

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

