

Mirathane™ H220

Thermoplastic Polyurethane Elastomer

Miracll Chemicals Co., Ltd.

Message:

Mirathane™ H220 is a Thermoplastic Polyurethane Elastomer product. It is available in Asia Pacific.

| General Information | | | |
|------------------------------|---------------|-------|-------------|
| Physical | Nominal Value | Unit | Test Method |
| Specific Gravity | 1.20 | g/cm³ | ASTM D792 |
| Viscosity - 15% MEK (25°C) | 2.00 | Pa·s | |
| Crystallization Rate | fast | | |
| Hardness | Nominal Value | Unit | Test Method |
| Durometer Hardness (Shore A) | 97 | | ASTM D2240 |
| Elastomers | Nominal Value | Unit | Test Method |
| Tensile Strength (Yield) | 30.0 | MPa | ASTM D412 |
| Tensile Elongation (Break) | 400 | % | ASTM D412 |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

