

NEXUS PE LLDPE-B118

Linear Low Density Polyethylene

Nexus Resin Group, LLC.

Message:

Linear Low Density Polyethylene for blown film applications

Nexus LLDPE-B118 is designed for blown film applications such as liners and stretch wrap. Available in various slip and antiblock packages.

General Information			
Uses	Film		
	Liners		
	Stretch Wrap		
Processing Method	Blown Film		
Physical	Nominal Value	Unit	Test Method
Density	0.918	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	1.0	g/10 min	ASTM D1238
Films	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D882
MD : Yield	35.9	MPa	
TD : Yield	24.8	MPa	
Tensile Elongation			ASTM D882
MD : Break	1500	%	
TD : Break	1500	%	
Dart Drop Impact	120	g	ASTM D1709

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT