

Fixmaster Wear Resistant Putty

Epoxy; Epoxide

Loctite®

Message:

Fixmaster Wear Resistant Putty is an Epoxy; Epoxide (Epoxy) product filled with ceramic fiber. It is available in North America. Applications of Fixmaster Wear Resistant Putty include coating applications and industrial applications. Primary characteristic: wear resistant.

General Information			
Filler / Reinforcement	Ceramic Fiber		
Features	Good Abrasion Resistance		
	Good Wear Resistance		
Uses	Industrial Applications		
	Protective Coatings		
Appearance	Grey		
Forms	Pellets		
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	41.4	MPa	ASTM D638
Compressive Strength	96.5	MPa	ASTM D695
Thermal	Nominal Value	Unit	Test Method
Continuous Use Temperature	93.3	°C	ASTM D794
Thermoset	Nominal Value	Unit	
Thermoset Components			
Hardener	Mix Ratio by Volume: 1.0		
Resin	Mix Ratio by Volume: 4.0		
Pot Life (25°C)	45	min	
Demold Time (25°C)	480	min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT