

# Indothene LL 20FY010

Linear Low Density Polyethylene

Reliance Industries Limited

## Message:

Indothene LL 20FY010 is a Linear Low Density Polyethylene product. It is available in Africa & Middle East or Asia Pacific.

General Information			
Forms	Granules		
Physical	Nominal Value	Unit	Test Method
Density	0.920	g/cm <sup>3</sup>	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	1.0	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Coefficient of Friction	0.22		ASTM D1894
Films	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D882
MD : Break	39.2	MPa	
TD : Break	29.4	MPa	
Tensile Elongation			ASTM D882
MD : Break	700	%	
TD : Break	800	%	
Dart Drop Impact	120	g	ASTM D1709
Elmendorf Tear Strength			ASTM D1922
MD	230	g	
TD	500	g	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

