

# DOW™ LLDPE NG 1045.11T

Linear Low Density Polyethylene Resin

The Dow Chemical Company

## Message:

LLDPE NG 1045.11T is a Linear Low Density Polyethylene Resin 1-Butene, 1-Octene terpolymer, produced in the SOLUTION process. This resin is designed to be used in blown extrusion to produce film for industrial & consumer applications.

General Information			
Additive	Antiblock (2500 ppm)		
	Slip (1000 ppm)		
Agency Ratings	FDA 21 CFR 177.1520(c) 3.2a		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.920	g/cm³	ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	1.0	g/10 min	ASTM D1238

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

