

# PVC Film 826

Flexible Polyvinyl Chloride

Teknor Apex Company

## Message:

PVC Film 826 is a flexible polyvinyl chloride material. This product is available in North America, Africa and the Middle East, Latin America, Europe or Asia Pacific.

Typical application areas include:

- Movie
- medical/health care

General Information			
Uses	Films		
	Medical/nursing supplies		
Forms	Particle		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.36	g/cm <sup>3</sup>	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore C, 10 sec)	79		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	22.1	MPa	ASTM D638
Tensile Elongation (Break)	280	%	ASTM D638
Additional Information			

拉伸保持率,7天老化,136°C:108%拉伸保持率,7天老化,136°C:78%冷弯曲,20°C,弯曲3次,1/16"心轴:合格尺寸稳定性,15分钟,212°F:6%可燃性,ASTM D568:S.E.

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519  
Phone: +86 13424755533  
Email: sales@su-jiao.com  
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

