

# KER® 1909

Rubber

Synthos S.A.

Message:

KER® 1909 is an off-grade of high styrene rubber, stabilized with non-staining antioxidant. It is allowed to have a form of irregular pellets, of pale cream to brown color.

APPLICATION

KER® 1909 is used for production of micro porous rubber, shoe soles, floor finishes and hard rubber articles.

| General Information |               |      |             |
|---------------------|---------------|------|-------------|
| Additive            | Antioxidant   |      |             |
| Features            | Antioxidant   |      |             |
| Uses                | Flooring      |      |             |
|                     | Footwear      |      |             |
| Forms               | Pellets       |      |             |
| Physical            | Nominal Value | Unit | Test Method |
| Organic Acid        | 3.5 to 7.0    | wt%  | ASTM D5774  |
| Volatile Matter     | < 1.8         | wt%  | ASTM D5668  |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

  
WECHAT