Epolene® N-11P

Low Density Polyethylene

Westlake Chemical Corporation

Message:

Epolene N-11P is a polyethylene (PE) homopolymer powder that can easily be melt blended with natural or synthetic waxes to increase the tensile strength of wax blends, improve the gloss of paper coatings, aid in pigment dispersion and mold release, and improve scuff and rub off resistance in printing inks. For these applications, six Epolene N-types, differing mainly in viscosity, are available to choose from (Epolene N-10, N-11, N-14, N-30, N-34, and N-35).

General Information				
Features	High Gloss			
	Homopolymer			
	Scratch Resistant			
Uses	Adhesives			
	Automotive Applications			
	Blending			
	Building Materials			
	Coating Applications			
	Construction Applications			
	Packaging			
	Plastics Modification			
	Printing Ink			
Forms	Powder			
Physical	Nominal Value			
Molecular Weight ¹	6000			
Softening Point - Mettler ²	107	°C		
Penetration Hardness ³ (25°C)	2.00	d mm	ASTM D5	
Fill Analysis	Nominal Value	Unit	Test Method	
Melt Viscosity (125°C)	350	mPa∙s		
NOTE				
		Molecular weight measured via Gel		
1.	Permeation Chromatograph (GPC) using polystyrene sta			
2.	ASTM D6090			
	Needle under 100-g load fo	r 5s,		
3.	tenths of mm			

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

