Abstron TG3MM

Acrylonitrile Butadiene Styrene

Bhansali Engineering Polymers Limited

Message:

Abstron TG3MM is an acrylonitrile butadiene styrene (ABS) product. It can be processed by injection molding and is available in the Asia-Pacific region. Features include:

flame retardant/rated flame

Hard

Impact resistance

General Information				
Features	Rigidity, high			
	Medium liquidity			
	Medium impact resistance			
Processing Method	Injection molding			
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.05	g/cm³	ASTM D792	
Melt Mass-Flow Rate (MFR) (220°C/10.0 kg)	21	g/10 min	ASTM D1238	
Molding Shrinkage - Flow	0.30 - 0.50	%	ASTM D955	
Hardness	Nominal Value	Unit	Test Method	
Rockwell Hardness (R-Scale, Injection Molded)	105		ASTM D785	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength			ASTM D638	
Yield, 3.20mm, injection molding ¹	45.1	MPa	ASTM D638	
Yield, 3.20mm, injection molding ²	49.0	МРа	ASTM D638	
Flexural Modulus ³ (6.40 mm, Injection Molded)	2300	MPa	ASTM D790	
Flexural Strength ⁴ (Yield, mm, injection molding)	68.6	MPa	ASTM D790	
Impact	Nominal Value	Unit	Test Method	
Notched Izod Impact			ASTM D256	
23°C, 3.20mm, injection molding	270	J/m	ASTM D256	
23°C, 6.40mm, injection molding	230	J/m	ASTM D256	
Thermal	Nominal Value	Unit	Test Method	
Deflection Temperature Under Load ⁵ (1.8 MPa, Annealed, 6.40 mm, Injection				
Molded)	90.0	°C	ASTM D648A	
Flammability	Nominal Value		Test Method	
Flame Rating (3.2 mm)	НВ		UL 94	

1.	Type 1, 5.0 mm/min
2.	Type 1, 50mm/min
3.	5.0 mm/min
4.	5.0 mm/min
5.	Annealed at 80°C for 2 hr

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

