

3M™ Dyneon™ Fluoroplastic THV 500GZ

Fluoroelastomer

3M Advanced Materials Division

Message:

Dyneon™ THV 500G Z Fluorothermoplastic is a flexible, transparent fluoroplastic composed of tetrafluoroethylene, and vinylidene fluoride in the form of pellets. It provides a balance of low temperature processing, low flammability, thermal stability, and melt processability. It can be used to prepare extruded films, tubes, profiles, and wire coatings. It is useful for applications that require flexibility, low temperature processing and good chemical resistance.

General Information			
Features	Bondability		
	Flame Retardant		
	Good Chemical Resistance		
	Good Flexibility		
	Good Thermal Stability		
	High Clarity		
Uses	Coating Applications		
	Film		
	Profiles		
	Tubing		
	Wire & Cable Applications		
Appearance	Clear/Transparent		
Forms	Pellets		
Processing Method	Film Extrusion		
	Profile Extrusion		
	Wire & Cable Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	1.98	g/cm ³	ISO 12086
Melt Mass-Flow Rate (MFR)	10	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Break)	26.0	MPa	ISO 527-1
Tensile Strain (Break)	500	%	ISO 527-1
Flexural Modulus	210	MPa	ASTM D790
Thermal	Nominal Value	Unit	Test Method
Melting Temperature	165	°C	ISO 12086
Flammability	Nominal Value	Unit	Test Method
Oxygen Index	> 75	%	ASTM D2863

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

