

Hyundai EP PPF HG960

Polypropylene Homopolymer

HYUNDAI EP Co., Ltd.

Message:

Hyundai EP PPF HG960 is a Polypropylene Homopolymer (PP Homopolymer) product filled with glass fiber. It is available in Asia Pacific. Applications of Hyundai EP PPF HG960 include electrical/electronic applications and housings. Primary characteristic: homopolymer.

General Information			
Filler / Reinforcement	Glass Fiber		
Features	Homopolymer		
Uses	Bobbins		
	Housings		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.13	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	115		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	82.1	MPa	ASTM D638
Tensile Elongation (Break)	13	%	ASTM D638
Flexural Modulus	4740	MPa	ASTM D790
Flexural Strength	93.6	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact			ASTM D256
-30°C	65	J/m	
23°C	95	J/m	
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	163	°C	ASTM D648

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

