ALFATER XL® A85I 2UV0000

Thermoplastic Vulcanizate

ALBIS PLASTIC GmbH

Message:

ALFATER XL® A85I 2UV0000 is a thermoplastic vulcanized rubber (TPV) product. It can be processed by injection molding and is available in North America, Europe or the Asia-Pacific region. ALFATER XL® The application areas of A85I 2UV0000 include engineering/industrial accessories, furniture, construction applications, hats/caps/corks and sealing applications.

Features include: Comply with REACH standard ROHS certification good weather resistance UV stability

General Information				
Additive	UV stabilizer			
Features	Ozone resistance			
	alkali resistance			
	Good weather resistance			
Uses	Handle			
	Shield			
	Furniture			
	Architectural application field			
	Seals			
	Application in Automobile Field			
	Knob			
Agency Ratings	EC 1907/2006 (REACH)			
RoHS Compliance	RoHS compliance			
Processing Method	Injection molding			
Physical	Nominal Value	Unit	Test Method	
Density	0.950	g/cm³	ISO 1183	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore A)	85		ISO 868	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Stress (100% Strain)	5.20	МРа	ISO 527-2	
Elastomers	Nominal Value	Unit	Test Method	
Tensile Stress (Yield)	11.6	МРа	ISO 37	
Tensile Elongation (Break)	550	%	ISO 37	
Tear Strength	51	kN/m	ISO 34-1	
Compression Set ¹ (100°C, 22 hr)	50	%	ISO 815	
Thermal	Nominal Value	Unit		

Service Temperature	-40 - 125	°C	
Injection	Nominal Value	Unit	
Drying Temperature	70 - 80	°C	
Drying Time	2.0 - 4.0	hr	
Processing (Melt) Temp	195 - 215	°C	
Mold Temperature	10 - 70	°C	
Injection Rate	Fast		
NOTE			
1.	25%		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

