Evermore PUR SS-168K

Polyurethane

Evermore Chemical Industry Co., Ltd.

Message:

Evermore PUR SS-168K is a Polyurethane product. It is available in Asia Pacific. Applications of Evermore PUR SS-168K include coating applications and fabrics/fibers. Primary characteristic: high gloss.

General Information			
Features	High Gloss		
Uses	Coating Applications		
	Textile Applications		
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (100% Strain)	0.981 to 2.94	MPa	ASTM D412
Tensile Strength (Yield)	11.8 to 24.5	MPa	ASTM D412
Tensile Elongation (Break)	500 to 800	%	ASTM D412
Fill Analysis	Nominal Value	Unit	Test Method
Melt Viscosity (25.0°C)	70.0 to 110	Pa·s	ASTM D3835
Additional Information	Nominal Value	Unit	Test Method
Non-Volatile Content	44 to 46	%	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

DMF, MEK, TOL

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Solvents

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

