

MTEGRITY™ LLDPE LL104AA

Linear Low Density Polyethylene

M. Holland Company

Message:

MTEGRITY™ LLDPE LL104AA is a Linear Low Density Polyethylene product. It is available in North America. Applications of MTEGRITY™ LLDPE LL104AA include bags/liners, film and packaging.

General Information			
Uses	Film		
	Liners		
	Packaging		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Density	0.918	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	1.0	g/10 min	ASTM D1238
Films	Nominal Value	Unit	Test Method
Secant Modulus			ASTM D882
1% Secant, MD	179	MPa	
1% Secant, TD	193	MPa	
Tensile Strength			ASTM D882
MD : Break	33.1	MPa	
TD : Break	27.6	MPa	
Tensile Elongation			ASTM D882
MD : Break	600	%	
TD : Break	800	%	
Dart Drop Impact	100	g	ASTM D1709
Elmendorf Tear Strength			ASTM D1922
MD	110	g	
TD	430	g	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT