

Braskem PP FPT350WV3

Polypropylene Homopolymer

Braskem America Inc.

Message:

Sub-group

Homopolymer

Description

Narrow molecular weight distribution, antistatic, nucleated, very good mold release

Applications

Suggested uses include fast-cycle injection molding, large-part injection molding, disposable drinkware

General Information			
Additive	Antistatic		
	Nucleating Agent		
Features	Antistatic		
	Disposable		
	Fast Molding Cycle		
	Food Contact Acceptable		
	Good Mold Release		
	Homopolymer		
	Narrow Molecular Weight Distribution		
	Nucleated		
Uses	Disposable Drinkware		
	Thick-walled Parts		
Agency Ratings	FDA 21 CFR 177.1520		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	35	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	106		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ¹ (Yield)	37.9	MPa	ASTM D638
Tensile Elongation ² (Yield)	8.0	%	ASTM D638
Flexural Modulus - 1% Secant ³	1660	MPa	ASTM D790A
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	27	J/m	ASTM D256A
NOTE			

1.	51 mm/min
2.	51 mm/min
3.	1.3 mm/min

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

