

# Hanwha Total PE PE30

Ethylene Vinyl Acetate Copolymer  
HANWHA TOTAL PETROCHEMICALS Co., Ltd.

Message:

PE30 is an easy peelable polypropylene compound is a blown and cast film resin designed to be a sealing layer for lidding or pouch applications. As a seal layer, this compound offers an extremely stable sealing strength over a wide range of heat seal temperature as well as clean and easy opening.

General Information	
Additive	Antioxidant
	Medium Antiblock
	Medium Slip
Features	Antioxidant
	Good Heat Seal
	Medium Antiblocking
	Medium Slip
Uses	Cast Film
	Lids
Forms	Pellets
Processing Method	Blown Film
	Cast Film

Physical	Nominal Value	Unit	Test Method
Density	0.920	g/cm <sup>3</sup>	ASTM D1505
Melt Mass-Flow Rate (MFR)	3.0	g/10 min	ASTM D1238
Optical	Nominal Value	Unit	Test Method
Haze	8.0	%	ASTM D1003
Extrusion	Nominal Value	Unit	
Cylinder Zone 1 Temp.	105	°C	
Cylinder Zone 2 Temp.	115	°C	
Cylinder Zone 3 Temp.	120	°C	
Adapter Temperature	120	°C	
Die Temperature	155 to 160	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

# Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

