

# Sylvin 8773-60D White 1430

Rigid Polyvinyl Chloride  
Sylvin Technologies Incorporated

Message:  
Sylvin 8773-60D White 1430 Is A Semi-rigid Vinyl Compound Formulated For Exterior Extruded Cap Stock Applications. This Compound Has Excellent Opacity For Thin Wall Applications And Also Offers Superior Weathering Characteristics.

General Information			
Features	Good weather resistance		
Uses	Thin wall parts		
	Shield		
	Building materials		
	Architectural application field		
Appearance	White		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.41	g/cm <sup>3</sup>	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shaw D	60		ASTM D2240
Shaw D, 10 seconds	60		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	23.4	MPa	ASTM D638
Tensile Elongation (Break)	200	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-12.0	°C	ASTM D746
Melting Temperature	177 - 191	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT