

HIPTEN® 15180

Low Density Polyethylene

HIP-PetroHemija

Message:

HIPTEN® 15180 is low density polyethylene resin for production of injection moulding articles and as a basis for masterbatches.

General Information			
Uses	Masterbatch		
Agency Ratings	EC 1907/2006 (REACH)		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.915	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	18	g/10 min	ISO 1133
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	96.0	°C	ISO 306
Injection	Nominal Value	Unit	
Processing (Melt) Temp	180 to 200	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

