

Sylvin 8476-90UV Red 6257

Polyvinyl Chloride
Sylvin Technologies Incorporated

Message:
Sylvin 8476-90UV Red 6257 Is A Vinyl/Polyurethane Compound Formulated For Extrusion Applications That Require Outdoor UV Stability, Excellent Ozone Resistance, Good Abrasion Resistance, Good Low Temperature Properties, And Ease Of Processing.

General Information			
Additive	UV Stabilizer		
Features	Good Abrasion Resistance		
	Good UV Resistance		
	Low Temperature Resistant		
	Oxidation Resistant		
Appearance	Red		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.25	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 10 sec)	90		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	17.9	MPa	ASTM D638
Tensile Elongation (Break)	350	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method
Tear Strength	101	kN/m	ASTM D624
Thermal	Nominal Value	Unit	
Melting Temperature	171 to 182	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT