# Relpet® G5841

### Polyethylene Terephthalate

#### **Reliance Industries Limited**

#### Message:

Relpet® G5841 is bottle grade PET resin manufactured using Du Pont's technology. It is typically used for: Aerated drinks. Agro chemicals APET sheet and PET strapping Relpet® G5841 is engineered to provide: Good process ability Excellent clarity/gloss Very Good mechanicals

| General Information |                                |      |                 |
|---------------------|--------------------------------|------|-----------------|
| Features            | Copolymer                      |      |                 |
|                     | Food Contact Acceptable        |      |                 |
|                     | Good Processability            |      |                 |
|                     | High Clarity                   |      |                 |
|                     | High Gloss                     |      |                 |
|                     |                                |      |                 |
| Uses                | Agricultural Chemicals Bottles |      |                 |
|                     | Bottles                        |      |                 |
|                     | Sheet                          |      |                 |
|                     | Strapping                      |      |                 |
|                     |                                |      |                 |
| Agency Ratings      | FDA 21 CFR 177.1630            |      |                 |
| Physical            | Nominal Value                  | Unit | Test Method     |
| Acetaldehyde        | < 1.0                          | ppm  | Internal Method |
| Color b - CIE       | -3.00 to 0.00                  |      | Internal Method |
| Crystallinity       | > 50                           | %    | Internal Method |
| Intrinsic Viscosity | 0.82 to 0.86                   | dl/g | ASTM D4603      |
| Chip Size           | 63.0 to 73.0                   |      | Internal Method |
| Fines               | < 100                          | ppm  | Internal Method |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

#### Tel: +86 21 5895 8519 Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

