

# Nipol® SBR 1739

Emulsion Styrene Butadiene Rubber

Zeon Corporation

## Message:

Nipol SBR is produced through emulsion polymerization and is superior to natural rubber in heat aging resistance, abrasion resistance, ozone resistance, chemical resistance, fire retardant performance, and gas penetrability. Furthermore, in terms of tensile strength and bending fracture resistance, performance that is nearly identical to natural rubber can be obtained by optimizing the composition. It is used in a variety of industrial rubber products, such as tires and footwear.

## Uses

Tire tread rubber for high performance tire.

General Information		
Additive	Antioxidant 2	
Features	Antioxidant	
Uses	Tires	
Physical	Nominal Value	Unit
Specific Gravity	0.978	g/cm <sup>3</sup>
Mooney Viscosity	49	MU
Bound Styrene	40.0	%
Oil Content - Highly Aromatic	38	phr

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT