

# Zeoforte® ZSC 4195CX

Acrylonitrile Butadiene Rubber

Zeon Chemicals L.P.

## Message:

Nano-Composite Hydrogenated Nitrile Rubber - Zeon Super Composite

Main Characteristics & Applications

Cold flexible Zetpol composite for use in low-temperature dynamic applications, e.g. timing belts.

General Information		
Features	Low Temperature Flexibility	
Uses	Belts/Belt Repair	
Physical	Nominal Value	Unit
Specific Gravity	1.25	g/cm <sup>3</sup>
Mooney Viscosity (ML 1+4, 100°C)	60 to 90	MU
Bound Acrylonitrile <sup>1</sup>	19.0	wt%
Iodine Value <sup>2</sup>	15.0	mg/100 mg
NOTE		
1.	Measured on base polymer.	
2.	Measured on base polymer.	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

  
WECHAT