

apilon 52bio® DB 40/AP

Thermoplastic Polyurethane Elastomer (Polyester)

API SpA

Message:

apilon 52bio® DB 40/AP is a Thermoplastic Polyurethane Elastomer (Polyester) (TPU-Polyester) product. It is available in Europe. Primary characteristic: eco-friendly/green.

General Information			
Features		Renewable Resource Content	
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.21	g/cm³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	37		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	45.0	MPa	ASTM D638
Tensile Elongation (Break)	730	%	ASTM D638
Abrasion Resistance	40.0	mm³	DIN 53516
Renewable Content	21	%	
Elastomers	Nominal Value	Unit	Test Method
Tear Strength	100	kN/m	ASTM D624

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT