

Evermore PUR SA-2321HR

Polyurethane

Evermore Chemical Industry Co., Ltd.

Message:

Evermore PUR SA-2321HR is a Polyurethane product. It is available in Asia Pacific. Typical application: Fabrics/Fibers. Primary characteristic: low temperature resistant.

General Information			
Features	Hydrolysis Resistant		
	Low Temperature Resistant		
Uses	Synthetic Leather		
	Textile Applications		
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (100% Strain)	0.981 to 3.43	MPa	ASTM D412
Tensile Strength (Yield)	9.81 to 24.5	MPa	ASTM D412
Tensile Elongation (Break)	300 to 600	%	ASTM D412
Fill Analysis	Nominal Value	Unit	Test Method
Melt Viscosity (25.0°C)	80.0 to 120	Pa·s	ASTM D3835
Additional Information	Nominal Value	Unit	Test Method
Non-Volatile Content	59 to 61	%	
Solvents	DMF, MEK		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT