

EPAMOULD 686A01

Thermoplastic Polyurethane Elastomer (Polyester)

Epaflex Polyurethanes S.R.L.

Message:

The EPAMOULD 600 series was created to meet the most stringent performance requirements in the footwear industry. Over time it has evolved to include the existing range of products, all made from polyester, which comprises:
a series of products plasticized, phthalate-free and high fluidity
a number of products to be free from plasticizers, robust and suitable to the technical sector.

General Information	
Additive	Beeswax
Uses	Footwear
Processing Method	Extrusion
	Injection molding

Physical	Nominal Value	Unit
Density	1.05	g/cm ³
Hardness	Nominal Value	Unit
Durometer Hardness (Shore A)	86	
Mechanical	Nominal Value	Unit
Abrasion Loss	85.0	mm ³

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

