

Durez® 33897

Phenolic

Sumitomo Bakelite North America, Inc.

Message:

Durez 33897 is an epoxy-modified, phenolic resin dissolved in Isopropyl Alcohol and Methyl Ethyl Ketone.

Durez 33897 is recommended for use in the manufacturing of clutches and torque converters.

High strength

High temperature resistance

Long wear

General Information			
Features	Good Wear Resistance		
	High Heat Resistance		
	High Strength		
Uses	Automotive Applications		
Appearance	Amber		
Forms	Liquid		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.980	g/cm ³	Internal Method
Thermoset	Nominal Value	Unit	Test Method
Thermoset Mix Viscosity (25°C)	90.0	cP	Internal Method
Post Cure Time (152°C)	0.029	hr	
Additional Information	Nominal Value	Unit	Test Method
Non-Volatile Content	41	%	Internal Method

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT