

WPP PPC4IMVJOSB26529-Black

Polypropylene Impact Copolymer

Washington Penn Plastic Co. Inc.

Message:

WPP PPC4IMVJOSB26529-Black is a Polypropylene Impact Copolymer (PP Impact Copolymer) product. It is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Typical application: Automotive.

Characteristics include:

- Copolymer
- Good Stiffness
- Impact Resistant

General Information			
Features	Good Stiffness		
	Impact Copolymer		
	Medium Impact Resistance		
Uses	Automotive Applications		
Appearance	Black		
	Colors Available		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.898	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	7.0	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ¹ (Yield)	26.0	MPa	ASTM D638
Flexural Modulus - Tangent ²	985	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Gardner Impact (-30°C)	12.0	J	ASTM D3029
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	85.0	°C	ASTM D648
NOTE			
1.	50 mm/min		
2.	1.3 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

